



Also included, clear rigid wallet, grey card infill, 2 x PVC tubes, 10 x recycling posters.


1.1 Fasten the 'P' clips (Part C) to the back of the bin ensuring the 'P' section is facing the outside edges of the bin. The clip is fastened through the location holes under the upper lip on the bin with the nylon washer (Part B) on the outer surface. The metal nut (Part E) is located in the inner surface and can be tightened using the spanner (Part G) provided.

1.2 Lay the bin on its front and pass each tube through a 'P' clip. Ensure the slotted section of the tube is at the top of the bin and that the slots







1.3 Pass the remaining screws through each of the locating holes near the base of each tube (diagram B). The remaining nuts can be loosely placed in position.



1.4 Push the tubes upwards until they reach the base of the bin and the screws are held in the locating slots at the base of the bin. Tighten the fixing screw and nut using the spanner and allen key provided (diagram C). The sign carrier comprises of a clear rigid wallet, a grey card infill and optional posters.



Place the chosen poster in front of the grey infill. (a second poster can be placed behind the grey infill so it can be visible from the rear of the unit necessary if the unit is being used back to back).





1.5 Place the grey infill and poster into the rigid wallet.

1.6 Slide the assembled wallet down in between the tubes until the hooks on the edge of the wallet locate at the base of each tube slot (diagram D). 1.7 Place the two caps in position on top of each tube (diagram E).

## 2. Wall Mounting Sign Kit

Parts included, clear rigid wallet, grey card infill, 2 x PVC tubes, 4 plastic caps, 5 x recycling posters, 2 x wall plugs, 2 x wall fixing screws.





- A planned maintenance schedule of regular inspection is recommended, replacing components as necessary.
- Replacement components are available direct from GLASDON.
- GLASDON cannot be held responsible for claims arising from incorrect installation, unauthorised modifications or misuse of the product

Issue 1 FEB. 2004 Stock no. C000/0261 Copyright Feb. 2004



2.7 Drill wall with a 5mm drill bit at the 2.8 Insert wall plugs ensuring they are 2.9 Using a hexagon head screw driver insert the screw onto the wall leaving 2.10 Hang the sign onto the screw heads



Glasdon U.K. Limited Preston New Road BLACKPOOL Lancashire FY4 4UL Tel: 01253 600410 Fax: 01253 792558 e-mail:sales@glasdon-uk.co.uk web:www.glasdon.com

5103/GM/2.04